

Armeringstol med spion



Armeringsstolen benyttes til å feste armeringsnett til PE-Skum. Armeringsstolen sikrer at nettet har 25mm overdekning mot PE-Skummet. I tillegg har armeringsstolen en indikator på 70 eller 75 mm, for å sikre rett tykkelse på sprøytebetongen. Armeringsstolen monteres i krysset på armeringsnett.

Lagerprogram:

Armeringsstol 70/25 m/spion sort

Armeringsstol 70/25 m/spion gul

Armeringsstol 75/25 m/spion rød

Teknisk informasjon:

Materiale: HDPE

Monteres med batteridrill påsatt 6kt. bits, NV= 10mm.

Produktet kan brukes i temperaturer ned til -10

***Gul og rød farge er **ikke** 100% resirkulerte.*

Tilbehør:

6kt. bits NC=10 mm.

Reinforcing mesh seat with spy



For use in attaching reinforcing mesh to PE foam. The seat ensures 25 mm of concrete cover between the mesh and PE foam. The seat has an indicator for 70 or 75 mm, to ensure the correct thickness of sprayed concrete. The seat should be mounted in the crossing of the reinforcement mesh to ensure that the mesh is adequately mounted.

Stock programme:

Reinforcing mesh seat 70/25 w/spy black
 Reinforcing mesh seat 70/25 w/spy yellow
 Reinforcing mesh seat 75/25 w/spy red

Technical information:

Material: HDPE
 Installed using a cordless power drill with a hexagonal bit.
 The product can be used in temperatures down to -10°C

** Yellow and red color are **not** 100% recycled.

Accessories:

Hexagonal bit NC = 10 mm.