



Cylinder	CHFA262
Max Bar	700

Max kN	255
Piston Area	36,4

Bar	kN	Ton
10	3,64	0,36
20	7,28	0,73
30	10,92	1,09
40	14,56	1,45
50	18,20	1,81
60	21,84	2,18
70	25,48	2,54
80	29,12	2,90
90	32,76	3,26
100	36,40	3,63
110	40,04	3,99
120	43,68	4,35
130	47,32	4,71
140	50,96	5,08
150	54,60	5,44
160	58,24	5,80
170	61,88	6,17
180	65,52	6,53
190	69,16	6,89
200	72,80	7,25
210	76,44	7,62
220	80,08	7,98
230	83,72	8,34
240	87,36	8,70
250	91,00	9,07
260	94,64	9,43
270	98,28	9,79
280	101,92	10,16
290	105,56	10,52
300	109,20	10,88
310	112,84	11,24
320	116,48	11,65
330	120,12	12,01
340	123,76	12,38
350	127,40	12,74

Bar	kN	Ton
360	131,04	13,06
370	134,68	13,42
380	138,32	13,78
390	141,96	14,14
400	145,60	14,51
410	149,24	14,87
420	152,88	15,23
430	156,52	15,60
440	160,16	15,96
450	163,80	16,32
460	167,44	16,68
470	171,08	17,05
480	174,72	17,41
490	178,36	17,77
500	182,00	18,13
510	185,64	18,50
520	189,28	18,86
530	192,92	19,22
540	196,56	19,59
550	200,20	19,95
560	203,84	20,31
570	207,48	20,67
580	211,12	21,04
590	214,76	21,40
600	218,40	21,76
610	222,04	22,12
620	225,68	22,49
630	229,32	22,85
640	232,96	23,21
650	236,60	23,57
660	240,24	23,94
670	243,88	24,30
680	247,52	24,66
690	251,16	25,03
700	254,80	25,39

www.pretec.no
post@pretec.no
 +47 69102460

