

Tetningsplugg



Tetningsplugg brukes til å sikre vanntett boltgjennomføring i bakskive. Tetningspluggen monteres i bakskiven på forhånd. For at tetningspluggen skal fungere etter sin hensikt, er det viktig at tetningspluggen ikke blir dratt frem og tilbake på bolten. Blir tetningspluggen skadet, kan den enkelt erstattes med en ny.

Lagerprogram:

M16 – M20 – M24 – M30 – M33

Teknisk informasjon:

Materiale: EPDM

Shore: 60° Shore IRHD +/- 5°

Farge: Grå

Toleranse: ISO 3302

Finish: SIS 162950 Classe M3

Ref. tegn: PTC-115-1, -2, -3, -4, -5

Tilbehør:

Bakplater

Sealing plug



Sealing plug to ensure watertight bolt insertion through back plates. The sealing plug is pre-mounted on the back plate. In order for the sealing plug to function as intended, it is important that the plug is not pulled back and forth on the bolt. If the sealing plug is damaged it can be easily replaced with a new one.

Stock programme:

M16 – M20 – M24 – M30 – M33

Technical information:

Material: EPDM

Shore: 60° Shore IRHD +/- 5°

Colour: Grey

Tolerance: ISO 3302

Finish: SIS 162950 Class M3

Ref. drawings: PTC-115-1, -2, -3, -4, -5

Accessories:

Back plate