

P-clips for gjengestang



P-clips anbefales ved gysing av helgjengede stenger (HGS). Dette er en fleksibel og enkel løsning for å sentrere og holde HGS på plass når de skal gyses fast i et borehull. Dette er typisk for tekniske bolter i tunneler, for eksempel. P-clips kan monteres fra siden der man ønsker. Antallet kan variere etter behov, hullets størrelse, vinkel, samt vekten/lengden av HGS, men det anbefales å bruke minst 2 stk per HGS.

Lagerprogram:

P-clips for M16 / hull Ø22-28

P-clips for M20 / hull Ø26-28

P-clips for M24 / hull Ø30-32

Teknisk informasjon:

Material: Nylon

Farge: Svart

Tilbehør:

Gjengesteng M16

Gjengesteng M20

Gjengesteng M24

Anbefalt borehull:

Gjengestang M16: Ø22-28

Gjengestang M20: Ø26-28

Gjengestang M24: Ø30-32

P-clips for threaded rod



P-clips are recommended when using fully threaded rods (HGS). This is a flexible and simple solution for centering and holding the HGS in place when they are to be bolted into a drill hole. This is typical for technical bolts in tunnels, for example. P-clips can be mounted from the side wherever desired. The number can vary according to need, the size of the hole, the angle, as well as the weight/length of the HGS, but it is recommended to use at least 2 pcs. per HGS.

Stock programme:

P-clips for M16 / hull \varnothing 22-28

P-clips for M20 / hull \varnothing 26-28

P-clips for M24 / hull \varnothing 30-32

Technical information:

Material: Nylon

Color: Black

Accessories:

Threaded rod M16

Threaded rod M20

Threaded rod M24

Recommended borehole:

Threaded rod M16: \varnothing 22-28

Threaded rod M20: \varnothing 26-28

Threaded rod M24: \varnothing 30-32