

# TBS EVO

## FLANGE HEAD SCREW



### C4 EVO COATING

Multilayer coating with a surface treatment of epoxy resin and aluminium flakes. No rust after 1440 hours of salt spray exposure test, as per ISO 9227. Can be used in service class 3 outdoor applications and under class C4 atmospheric corrosion conditions.

### INTEGRATED WASHER


The flange head serves as washer and ensures high head strength and pull-through. Ideal in the presence of wind or variations in timber dimensions.

### AUTOCLAVE-TREATED TIMBER


The C4 EVO coating has been certified according to US acceptance criterion AC257 for outdoor use in ACQ-treated wood.

### T3 TIMBER CORROSIVITY

Coating suitable for use in applications on wood with an acidity level (pH) greater than 4, such as spruce, larch and pine (see page 314).



|                         |  |
|-------------------------|--|
| DIAMETER [mm]           | 6 <b>6</b> 10 16                                       |
| LENGTH [mm]             | 40 <b>60</b> 400 1000                                  |
| SERVICE CLASS           | <b>SC1</b> SC2 SC3                                     |
| ATMOSPHERIC CORROSIVITY | C1 <b>C2</b> C3 C4                                     |
| WOOD CORROSIVITY        | T1 <b>T2</b> T3  |
| MATERIAL                | <b>C4</b> EVO COATING carbon steel with C4 EVO coating |



### FIELDS OF USE

- timber based panels
- solid timber and glulam
- CLT and LVL
- high density woods
- ACQ, CCA treated timber



## OUTDOOR WALKWAYS

Ideal for the construction of outdoor structures such as walkways and arcades. Values also certified for screw insertion parallel to the grain. Ideal for fastening aggressive woods containing tannins.

## SIP PANELS

Values also tested, certified and calculated for CLT and high density woods such as Microllam® LVL. Suitable for fastening SIP and sandwich panels.




Fastening Wood Trusses outdoors.



Multi-ply beam fastening.

## GEOMETRY AND MECHANICAL CHARACTERISTICS



### GEOMETRY

| Nominal diameter                          | $d_1$     | [mm] | 6     | 8     | 10    |
|---|-----------|------|-------|-------|-------|
| Head diameter                             | $d_k$     | [mm] | 15,50 | 19,00 | 25,00 |
| Thread diameter                           | $d_2$     | [mm] | 3,95  | 5,40  | 6,40  |
| Shank diameter                            | $d_s$     | [mm] | 4,30  | 5,80  | 7,00  |
| Pre-drilling hole diameter <sup>(1)</sup> | $d_{v,S}$ | [mm] | 4,0   | 5,0   | 6,0   |
| Pre-drilling hole diameter <sup>(2)</sup> | $d_{v,H}$ | [mm] | 4,0   | 6,0   | 7,0   |

<sup>(1)</sup> Pre-drilling valid for softwood.

<sup>(2)</sup> Pre-drilling valid for hardwood and beech LVL.

### CHARACTERISTIC MECHANICAL PARAMETERS

| Nominal diameter | $d_1$        | [mm] | 6    | 8    | 10   |
|------------------|--------------|------|------|------|------|
| Tensile strength | $f_{tens,k}$ | [kN] | 11,3 | 20,1 | 31,4 |
| Yield moment     | $M_{y,k}$    | [Nm] | 9,5  | 20,1 | 35,8 |

|                                 |              |                      | softwood<br>(softwood) | LVL softwood<br>(LVL softwood) | pre-drilled beech LVL<br>(beech LVL predrilled) |
|---------------------------------|--------------|----------------------|------------------------|--------------------------------|---|
| Withdrawal resistance parameter | $f_{ax,k}$   | [N/mm <sup>2</sup> ] | 11,7                   | 15,0                           | 29,0  |
| Head-pull-through parameter     | $f_{head,k}$ | [N/mm <sup>2</sup> ] | 10,5                   | 20,0                           | -   |
| Associated density              | $\rho_a$     | [kg/m <sup>3</sup> ] | 350                    | 500                            | 730   |
| Calculation density             | $\rho_k$     | [kg/m <sup>3</sup> ] | ≤ 440                  | 410 ÷ 550                      | 590 ÷ 750                                       |


For applications with different materials please see ETA-11/0030.

## CODES AND DIMENSIONS

| $d_1$<br>[mm] | $d_k$<br>[mm] | CODE       | L<br>[mm] | b<br>[mm]  | A<br>[mm] | pcs |
|---------------|---------------|------------|-----------|------------|-----------|-----|
| 6<br>TX 30    | 15,5          | TBSEVO660  | 60        | 40         | 20        | 100 |
|               |               | TBSEVO680  | 80        | 50         | 30        | 100 |
|               |               | TBSEVO6100 | 100       | 60         | 40        | 100 |
|               |               | TBSEVO6120 | 120       | 75         | 45        | 100 |
|               |               | TBSEVO6140 | 140       | 75         | 65        | 100 |
|               |               | TBSEVO6160 | 160       | 75         | 85        | 100 |
|               |               | TBSEVO6180 | 180       | 75         | 105       | 100 |
|               |               | TBSEVO6200 | 200       | 75         | 125       | 100 |
|               |               | 8<br>TX 40 | 19,0      | TBSEVO8100 | 100       | 52  |
| TBSEVO8120    | 120           |            |           | 80         | 40        | 50  |
| TBSEVO8140    | 140           |            |           | 80         | 60        | 50  |
| TBSEVO8160    | 160           |            |           | 100        | 60        | 50  |
| TBSEVO8180    | 180           |            |           | 100        | 80        | 50  |
| TBSEVO8200    | 200           |            |           | 100        | 100       | 50  |
| TBSEVO8220    | 220           |            |           | 100        | 120       | 50  |
| TBSEVO8240    | 240           |            |           | 100        | 140       | 50  |
| TBSEVO8280    | 280           |            |           | 100        | 180       | 50  |
| TBSEVO8320    | 320           |            |           | 100        | 220       | 50  |
| TBSEVO8360    | 360           | 100        | 260       | 50         |           |     |
| TBSEVO8400    | 400           | 100        | 300       | 50         |           |     |



| $d_1$<br>[mm] | $d_k$<br>[mm] | CODE        | L<br>[mm] | b<br>[mm] | A<br>[mm] | pcs |
|---------------|---------------|-------------|-----------|-----------|-----------|-----|
| 10<br>TX 50   | 25,0          | TBSEVO10120 | 120       | 60        | 60        | 50  |
|               |               | TBSEVO10140 | 140       | 60        | 80        | 50  |
|               |               | TBSEVO10160 | 160       | 80        | 80        | 50  |
|               |               | TBSEVO10180 | 180       | 80        | 100       | 50  |
|               |               | TBSEVO10200 | 200       | 100       | 100       | 50  |
|               |               | TBSEVO10220 | 220       | 100       | 120       | 50  |
|               |               | TBSEVO10240 | 240       | 100       | 140       | 50  |
|               |               | TBSEVO10280 | 280       | 100       | 180       | 50  |

### WBAZ WASHER




| CODE     | screw<br>[mm] | $D_2$<br>[mm] | H<br>[mm] | $D_1$<br>[mm] | pcs |
|----------|---------------|---------------|-----------|---------------|-----|
| WBAZ25A2 | 6,0 - 6,5     | 25            | 15        | 6,5           | 100 |


## INSTALLATION




Correct tightening



Excessive tightening




Insufficient tightening



Tightening off axis

NOTE: The thickness of the washer after installation is approximately 8-9 mm.  
The maximum thickness of the fastening package was calculated by ensuring a minimum penetration length into the wood of 4 d.

| TBS EVO + WBAZ<br>$\varnothing \times L$ | fastening package<br>[mm] |
|--|---------------------------|
| 6 x 60                                   | min. 0 - max. 30          |
| 6 x 80                                   | min. 10 - max. 50         |
| 6 x 100                                  | min. 30 - max. 70         |
| 6 x 120                                  | min. 50 - max. 90         |
| 6 x 140                                  | min. 70 - max. 110        |
| 6 x 160                                  | min. 90 - max. 130        |
| 6 x 180                                  | min. 110 - max. 150       |
| 6 x 200                                  | min. 130 - max. 170       |





### FASTENING METAL SHEET

Can be installed on sheets up to 0,7 mm thick without pre-drilling. TBS EVO  $\varnothing 6$  mm is ideal when used in combination with washer WBAZ. For outdoor use (Service class 3).



## MINIMUM DISTANCES FOR SHEAR LOADS



screws inserted **WITHOUT** pre-drilled hole  $\rho_k \leq 420 \text{ kg/m}^3$



| $d_1$ [mm]     |      | 6  | 8   | 10  |
|----------------|------|----|-----|-----|
| $a_1$ [mm]     | 10·d | 60 | 80  | 100 |
| $a_2$ [mm]     | 5·d  | 30 | 40  | 50  |
| $a_{3,t}$ [mm] | 15·d | 90 | 120 | 150 |
| $a_{3,c}$ [mm] | 10·d | 60 | 80  | 100 |
| $a_{4,t}$ [mm] | 5·d  | 30 | 40  | 50  |
| $a_{4,c}$ [mm] | 5·d  | 30 | 40  | 50  |

| $d_1$ [mm]     |      | 6  | 8  | 10  |
|----------------|------|----|----|-----|
| $a_1$ [mm]     | 5·d  | 30 | 40 | 50  |
| $a_2$ [mm]     | 5·d  | 30 | 40 | 50  |
| $a_{3,t}$ [mm] | 10·d | 60 | 80 | 100 |
| $a_{3,c}$ [mm] | 10·d | 60 | 80 | 100 |
| $a_{4,t}$ [mm] | 10·d | 60 | 80 | 100 |
| $a_{4,c}$ [mm] | 5·d  | 30 | 40 | 50  |



screws inserted **WITHOUT** pre-drilled hole  $420 \text{ kg/m}^3 < \rho_k \leq 500 \text{ kg/m}^3$



| $d_1$ [mm]     |      | 6   | 8   | 10  |
|----------------|------|-----|-----|-----|
| $a_1$ [mm]     | 15·d | 90  | 120 | 150 |
| $a_2$ [mm]     | 7·d  | 42  | 56  | 70  |
| $a_{3,t}$ [mm] | 20·d | 120 | 160 | 200 |
| $a_{3,c}$ [mm] | 15·d | 90  | 120 | 150 |
| $a_{4,t}$ [mm] | 7·d  | 42  | 56  | 70  |
| $a_{4,c}$ [mm] | 7·d  | 42  | 56  | 70  |

| $d_1$ [mm]     |      | 6  | 8   | 10  |
|----------------|------|----|-----|-----|
| $a_1$ [mm]     | 7·d  | 42 | 56  | 70  |
| $a_2$ [mm]     | 7·d  | 42 | 56  | 70  |
| $a_{3,t}$ [mm] | 15·d | 90 | 120 | 150 |
| $a_{3,c}$ [mm] | 15·d | 90 | 120 | 150 |
| $a_{4,t}$ [mm] | 12·d | 72 | 96  | 120 |
| $a_{4,c}$ [mm] | 7·d  | 42 | 56  | 70  |


screws inserted **WITH** pre-drilled hole



| $d_1$ [mm]     |      | 6  | 8  | 10  |
|----------------|------|----|----|-----|
| $a_1$ [mm]     | 5·d  | 30 | 40 | 50  |
| $a_2$ [mm]     | 3·d  | 18 | 24 | 30  |
| $a_{3,t}$ [mm] | 12·d | 72 | 96 | 120 |
| $a_{3,c}$ [mm] | 7·d  | 42 | 56 | 70  |
| $a_{4,t}$ [mm] | 3·d  | 18 | 24 | 30  |
| $a_{4,c}$ [mm] | 3·d  | 18 | 24 | 30  |

| $d_1$ [mm]     |     | 6  | 8  | 10 |
|----------------|-----|----|----|----|
| $a_1$ [mm]     | 4·d | 24 | 32 | 40 |
| $a_2$ [mm]     | 4·d | 24 | 32 | 40 |
| $a_{3,t}$ [mm] | 7·d | 42 | 56 | 70 |
| $a_{3,c}$ [mm] | 7·d | 42 | 56 | 70 |
| $a_{4,t}$ [mm] | 7·d | 42 | 56 | 70 |
| $a_{4,c}$ [mm] | 3·d | 18 | 24 | 30 |

$\alpha$  = load-to-grain angle  
 $d = d_1$  = nominal screw diameter



### NOTES

- The minimum distances comply with the EN 1995:2014 standard in accordance with ETA-11/0030.
- The minimum spacing for all panel-to-timber connections ( $a_1$ ,  $a_2$ ) can be multiplied by a coefficient of 0,85.
- In the case of joints with elements in Douglas fir (*Pseudotsuga menziesii*), the minimum spacing and distances parallel to the grain must be multiplied by a coefficient of 1.5.
- The spacing  $a_1$  in the table for screws with 3 THORNS tip inserted without pre-drilling hole in timber elements with density  $\rho_k \leq 420 \text{ kg/m}^3$  and load-to-grain angle  $\alpha = 0^\circ$  was assumed to be 10·d based on experimental tests; alternatively, adopt 12·d in accordance with EN 1995:2014.

| geometry               |           |           |           | SHEAR                                      |   |                          | TENSION  |   |                             |                             |
|------------------------|-----------|-----------|-----------|--|---|--------------------------|--|---|-----------------------------|-----------------------------|
|                        |           |           |           | timber-to-timber<br>$\varepsilon=90^\circ$ | timber-to-timber<br>$\varepsilon=0^\circ$ | panel-to-timber          | thread<br>withdrawal<br>$\varepsilon=90^\circ$ | thread<br>withdrawal<br>$\varepsilon=0^\circ$ | head<br>pull-through        |                             |
|                        |           |           |           |  |   |                          |  |   |                             |                             |
| d <sub>1</sub><br>[mm] | L<br>[mm] | b<br>[mm] | A<br>[mm] | R <sub>V,90,k</sub><br>[kN]                | R <sub>V,0,k</sub><br>[kN]                | S <sub>PAN</sub><br>[mm] | R <sub>V,k</sub><br>[kN]                       | R <sub>ax,90,k</sub><br>[kN]                  | R <sub>ax,0,k</sub><br>[kN] | R <sub>head,k</sub><br>[kN] |
| 6                      | 60        | 40        | 20        | 1,89                                       | 1,02                                      | 50                       | -  | 3,03  | 0,91                        | 2,72                        |
|                        | 80        | 50        | 30        | 2,15                                       | 1,37                                      |                          | 2,14   | 3,79  | 1,14                        | 2,72                        |
|                        | 100       | 60        | 40        | 2,35                                       | 1,58                                      |                          | 2,50   | 4,55  | 1,36                        | 2,72                        |
|                        | 120       | 75        | 45        | 2,35                                       | 1,69                                      |                          | 2,50   | 5,68  | 1,70                        | 2,72                        |
|                        | 140       | 75        | 65        | 2,35                                       | 1,69                                      |                          | 2,50   | 5,68  | 1,70                        | 2,72                        |
|                        | 160       | 75        | 85        | 2,35                                       | 1,69                                      |                          | 2,50   | 5,68  | 1,70                        | 2,72                        |
|                        | 180       | 75        | 105       | 2,35                                       | 1,69                                      |                          | 2,50   | 5,68  | 1,70                        | 2,72                        |
|                        | 200       | 75        | 125       | 2,35                                       | 1,69                                      |                          | 2,50   | 5,68  | 1,70                        | 2,72                        |
| 8                      | 100       | 52        | 48        | 3,71                                       | 1,95                                      | 65                       | 3,22   | 5,25  | 1,58                        | 4,09                        |
|                        | 120       | 80        | 40        | 3,41                                       | 2,54                                      |                          | 3,89   | 8,08  | 2,42                        | 4,09                        |
|                        | 140       | 80        | 60        | 3,71                                       | 2,61                                      |                          | 3,89   | 8,08  | 2,42                        | 4,09                        |
|                        | 160       | 100       | 60        | 3,71                                       | 2,79                                      |                          | 3,89   | 10,10   | 3,03                        | 4,09                        |
|                        | 180       | 100       | 80        | 3,71                                       | 2,79                                      |                          | 3,89   | 10,10   | 3,03                        | 4,09                        |
|                        | 200       | 100       | 100       | 3,71                                       | 2,79                                      |                          | 3,89   | 10,10   | 3,03                        | 4,09                        |
|                        | 220       | 100       | 120       | 3,71                                       | 2,79                                      |                          | 3,89   | 10,10   | 3,03                        | 4,09                        |
|                        | 240       | 100       | 140       | 3,71                                       | 2,79                                      |                          | 3,89   | 10,10   | 3,03                        | 4,09                        |
|                        | 280       | 100       | 180       | 3,71                                       | 2,79                                      |                          | 3,89   | 10,10   | 3,03                        | 4,09                        |
|                        | 320       | 100       | 220       | 3,71                                       | 2,79                                      |                          | 3,89   | 10,10   | 3,03                        | 4,09                        |
|                        | 360       | 100       | 260       | 3,71                                       | 2,79                                      |                          | 3,89   | 10,10   | 3,03                        | 4,09                        |
|                        | 400       | 100       | 300       | 3,71                                       | 2,79                                      |                          | 3,89   | 10,10   | 3,03                        | 4,09                        |
| 10                     | 120       | 60        | 60        | 5,64                                       | 2,75                                      | 80                       | -  | 7,58  | 2,27                        | 7,08                        |
|                        | 140       | 60        | 80        | 5,64                                       | 2,75                                      |                          | 5,84   | 7,58  | 2,27                        | 7,08                        |
|                        | 160       | 80        | 80        | 5,64                                       | 3,28                                      |                          | 5,85   | 10,10   | 3,03                        | 7,08                        |
|                        | 180       | 80        | 100       | 5,64                                       | 3,28                                      |                          | 5,85   | 10,10   | 3,03                        | 7,08                        |
|                        | 200       | 100       | 100       | 5,64                                       | 3,87                                      |                          | 5,85   | 12,63   | 3,79                        | 7,08                        |
|                        | 220       | 100       | 120       | 5,64                                       | 3,87                                      |                          | 5,85   | 12,63   | 3,79                        | 7,08                        |
|                        | 240       | 100       | 140       | 5,64                                       | 3,87                                      |                          | 5,85   | 12,63   | 3,79                        | 7,08                        |
|                        | 280       | 100       | 180       | 5,64                                       | 3,87                                      |                          | 5,85   | 12,63   | 3,79                        | 7,08                        |

$\varepsilon$  = screw-to-grain angle

**GENERAL PRINCIPLES**

- Characteristic values consistent with EN 1995:2014 and in accordance with ETA-11/0030.
- Design values can be obtained from characteristic values as follows:

$$R_d = \frac{R_k \cdot k_{mod}}{\gamma_M}$$

The coefficients  $\gamma_M$  and  $k_{mod}$  should be taken according to the current regulations used for the calculation.

- For the mechanical resistance values and the geometry of the screws, reference was made to ETA-11/0030.
- Sizing and verification of the timber elements and panels must be done separately.
- The screws must be positioned in accordance with the minimum distances.
- The characteristic shear resistances are calculated for screws inserted without pre-drilling hole. In the case of screws inserted with pre-drilling hole, greater resistance values can be obtained.
- Shear strengths were calculated considering the threaded part fully inserted in the second element.
- The characteristic panel-timber shear strength are calculated considering an OSB panel or particle board with a  $S_{PAN}$  thickness and density  $\rho_k = 500 \text{ kg/m}^3$ .
- The thread withdrawal characteristic strength has been evaluated considering a fixing length equal to b.
- The head pull-through characteristic strength was calculated using timber elements.

- For minimum distances and structural values on CLT and LVL see TBS on page 76.
- For different calculation configurations, the MyProject software is available ([www.rothoblaas.com](http://www.rothoblaas.com)).

**NOTES**

- The characteristic timber-to-timber shear strengths were evaluated considering both an  $\varepsilon$  angle of  $90^\circ$  ( $R_{V,90,k}$ ) and  $0^\circ$  ( $R_{V,0,k}$ ) between the grains of the second element and the connector.
- The characteristic panel-timber shear strengths were evaluated considering an angle  $\varepsilon$  of  $90^\circ$  between the grains of the timber element and the connector.
- The characteristic thread withdrawal resistances were evaluated considering both an  $\varepsilon$  angle of  $90^\circ$  ( $R_{ax,90,k}$ ) and of  $0^\circ$  ( $R_{ax,0,k}$ ) between the grains of the timber element and the connector.
- For the calculation process a timber characteristic density  $\rho_k = 385 \text{ kg/m}^3$  has been considered. For different  $\rho_k$  values, the strength values in the table (timber-to-timber shear and tensile strength) can be converted using the  $k_{dens}$  coefficient (see page 87).
- For a row of n screws arranged parallel to the direction of the grain at a distance  $a_1$ , the characteristic effective shear bearing capacity  $R_{ef,V,k}$  can be calculated by means of the effective number  $n_{ef}$  (see page 80).