

Environmental product declaration

In accordance with ISO 14025 and EN15804+A2

Drillpipe - PD55™ | High Efficient Pipe Umbrella System



Let's connect

EPD-Global

Owner of the declaration:

Pretec Norge AS

Product:

Drillpipe - PD55™ | High Efficient Pipe Umbrella System

Declared unit:

1 kg

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR

outdated - NPCR 013:2019 Part B for Steel and aluminium construction products

Program operator:

EPD-Global

Declaration number:

NEPD-17013-21144

Issue date:

14.07.2026

Valid to:

14.07.2031

EPD software:

LCAno EPD generator ID: 1596044

General information

Product

Drillpipe - PD55™ | High Efficient Pipe Umbrella System

Program operator:

EPD-Global
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-global.com

Declaration number:

NEPD-17013-21144

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
outdated - NPCR 013:2019 Part B for Steel and aluminium
construction products

Statement of liability:

The owner of the declaration shall be liable for the underlying
information and evidence. EPD-Global shall not be liable with respect
to manufacturer information, life cycle assessment data and
evidences.

Declared unit:

1 kg Drillpipe - PD55™ | High Efficient Pipe Umbrella System

Declared unit with option:

A1-A3, A4, A5, C1, C2, C3, C4, D

Functional unit:

1 kg of Drillpipe - PD55™

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information
and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4.
Verification of each EPD is made according to EPD-Global's guidelines
for verification and approval requiring that tools are i) integrated into
the company's environmental management system, ii) the procedures
for use of the EPD tool are approved by EPD-Global, and iii) the
process is reviewed annually by an independent third party verifier.
See Appendix G of EPD-Global's General Programme Instructions for
further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data
and test-EPD in accordance with EPD-Global's procedures and
guidelines for verification and approval of EPD tools.

Third party verifier:

Alexander Borg, Asplan Viak AS

(no signature required)

Owner of the declaration:

Pretec Norge AS
Contact person: Ernad Sarajlija
Phone: (+47) 69 10 24 60
e-mail: post@pretec.no

Manufacturer:

Pretec Norge AS
Kampenesmosen 3
1739 Borgenhaugen, Norway

Place of production:

Pretec China
Zhejiang Pretec Metal Products Co., Ltd. Nr.9, Jinchang Rd, Haining
Zhejiang Province, P.R., China

Management system:

ISO 14001, ISO 9001 and ISO45001, AAA Certification AB, sert no
794 - EN 1090-1, AAA Certification AB, sert no 2296

Organisation no:

NO 980 429 245 MVA

Issue date:

14.07.2026

Valid to:

14.07.2031

Year of study:

2025

Comparability:

EPDs of construction products may not be comparable if they do not
comply with EN 15804 and are not viewed in a building context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03,
developed by LCA.no. The EPD tool is integrated in the company's
management system, and has been approved by EPD-Global.
Approval number:

Developer of EPD: Mikael Tangen

Reviewer of company-specific input data and EPD: Ernad Sarajlija

Approved:



Håkon Hauan, CEO EPD-Global

Product

Product description:

High Efficiency Pipe Umbrella System for automated installation using the standard rod handling magazine of a tunnel jumbo. The pipe is supplied with a female thread at one end and a male thread at the other. Used for spiling, forepoling and pipe umbrella support in difficult ground conditions in tunnels and caverns.

Product specification

PD55 drillpipe Ø55/23x3135 T45

Materials	kg	%
Metal - Steel	1.00	100.00
Total	1.00	100.00

Packaging	kg	%
Packaging - Pallet	0.022	95.65
Packaging - Plastic	0.001	4.35
Total incl. packaging	1.02	100.00

Technical data:

Made from seamless steel pipes Ø55/23.
Standard length 3,135 m.

Market:

Worldwide

Reference service life, product

Not relevant

Reference service life, building or construction works

Not relevant

LCA: Calculation rules

Declared unit:

1 kg Drillpipe - PD55™ | High Efficient Pipe Umbrella System

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.


Materials	Source	Data quality	Year
Metal - Steel	Modified ecoinvent 3.6	Database	2019
Packaging - Pallet	Modified ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage								End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use		De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7		C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND		X	X	X	X	X

System boundary:

This EPD is a "cradle-to-gate with options" EPD. The system boundary for this LCA report is from A1-A4, C1-C4 and D



Additional technical information:

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Module C " end of life stage" is a generic scenario for decommissioning of construction. Subject to project specific condition. Grade of recycling for different steel grades is based on statistics obtained from norsk stålforbund

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (km)	38.8 %	300.00	0.044	l/tkm	13.20
De-construction demolition (C1)	Unit	Value			
Diesel, burned (MJ)	MJ	0.626			
Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (km)	38.8 %	85.00	0.044	l/tkm	3.74
Waste processing (C3)	Unit	Value			
Materials to recycling (kg)	kg	0.8964			
Waste treatment per kg Hazardous waste, incineration (kg) - C3	kg	0.005			
Disposal (C4)	Unit	Value			
Waste, scrap steel, to landfill (kg)	kg	0.0996			
Landfilling of ashes from incineration of Hazardous waste, from incineration (kg) - C4	kg	0.000945			
Benefits and loads beyond the system boundaries (D)	Unit	Value			
Substitution of primary steel with net scrap (kg)	kg	0.05749			
Substitution of Zinc (kg)	kg	0.0179			
Substitution of thermal energy, district heating, in Norway (MJ)	MJ	0.00009125			
Substitution of electricity, in Norway (MJ)	MJ	0.000006032			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact										
Indicator		Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
	GWP-total	kg CO ₂ -eq	8.57E-01	5.70E-02	0	5.73E-02	1.62E-02	1.11E-02	8.40E-04	-1.18E-01
	GWP-fossil	kg CO ₂ -eq	8.88E-01	5.69E-02	0	5.73E-02	1.61E-02	1.11E-02	8.39E-04	-1.17E-01
	GWP-biogenic	kg CO ₂ -eq	-3.17E-02	4.40E-05	0	1.07E-05	1.25E-05	2.78E-05	5.27E-07	-5.56E-04
	GWP-luluc	kg CO ₂ -eq	7.45E-04	2.04E-05	0	4.52E-06	5.79E-06	2.80E-06	1.23E-07	-2.08E-04
	ODP	kg CFC11 -eq	5.86E-08	1.20E-09	0	1.24E-08	3.40E-10	1.27E-09	2.28E-10	-4.47E-08
	AP	mol H+ -eq	5.04E-03	1.18E-04	0	6.00E-04	3.36E-05	1.63E-05	4.98E-06	-8.46E-04
	EP-FreshWater	kg P -eq	3.68E-05	3.83E-06	0	2.09E-07	1.09E-06	2.66E-07	7.18E-09	-1.01E-05
	EP-Marine	kg N -eq	1.12E-03	2.85E-05	0	2.65E-04	8.06E-06	3.37E-06	1.77E-06	-1.82E-04
	EP-Terrestrial	mol N -eq	1.14E-02	3.07E-04	0	2.90E-03	8.70E-05	3.79E-05	1.97E-05	-1.99E-03
	POCP	kg NMVOC -eq	4.09E-03	1.97E-04	0	7.98E-04	5.58E-05	1.06E-05	5.61E-06	-6.48E-04
	ADP-minerals&metals ¹	kg Sb-eq	3.02E-05	1.90E-07	0	8.80E-08	5.37E-08	3.87E-08	4.48E-09	-1.39E-03
	ADP-fossil ¹	MJ	1.03E+01	8.01E-01	0	7.89E-01	2.27E-01	4.65E-02	1.57E-02	-1.33E+00
	WDP ¹	m ³	1.22E+01	3.98E-03	0	1.68E-01	1.13E-03	1.72E-01	7.83E-02	1.26E+00

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9.0 E-03 = 9.0*10⁻³ = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

GWP (A1-A3) reduced by 72% compared to 2023

Additional environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
 PM	Disease incidence	1.21E-07	4.20E-09	0	1.59E-08	1.19E-09	2.50E-10	9.30E-11	-7.35E-09
 IRP ²	kgBq U235 -eq	2.20E-02	1.03E-03	0	3.38E-03	2.93E-04	2.12E-04	7.05E-05	-5.66E-03
 ETP-fw ¹	CTUe	2.65E+01	1.07E-01	0	4.31E-01	3.02E-02	2.26E-01	1.24E-02	-6.32E+00
 HTP-c ¹	CTUh	1.04E-08	0.00E+00	0	1.70E-11	0.00E+00	1.10E-11	0.00E+00	-6.14E-10
 HTP-nc ¹	CTUh	3.24E-07	6.00E-10	0	3.96E-10	1.70E-10	6.50E-11	1.50E-11	-2.37E-09
 SQP ¹	dimensionless	4.40E+00	4.84E-01	0	1.00E-01	1.37E-01	1.83E-02	5.56E-02	-4.10E-01

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

"Reading example: 9.0 E-03 = 9.0×10^{-3} = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use										
Indicator		Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
	PERE	MJ	7.78E+00	1.40E-02	0	4.27E-03	3.97E-03	8.39E-03	4.48E-04	-1.50E-01
	PERM	MJ	3.05E-01	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PERT	MJ	8.08E+00	1.40E-02	0	4.27E-03	3.97E-03	8.39E-03	4.48E-04	-1.50E-01
	PENRE	MJ	1.03E+01	8.01E-01	0	7.89E-01	2.27E-01	4.65E-02	1.57E-02	-1.33E+00
	PENRM	MJ	4.25E-02	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PENRT	MJ	1.03E+01	8.01E-01	0	7.89E-01	2.27E-01	4.65E-02	1.57E-02	-1.33E+00
	SM	kg	1.00E+00	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	RSF	MJ	9.71E-03	4.70E-06	0	1.05E-04	1.33E-06	1.85E-04	8.67E-06	-6.25E-04
	NRSF	MJ	1.05E-01	0.00E+00	0	1.54E-03	0.00E+00	0.00E+00	5.50E-05	6.36E-02
	FW	m ³	1.39E-02	1.09E-04	0	4.06E-05	3.09E-05	4.31E-05	1.98E-05	-1.83E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9.0 E-03 = 9.0*10⁻³ = 0.009"

End of life - Waste										
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
	HWD	kg	3.83E-03	1.16E-03	0	2.32E-05	3.30E-04	0.00E+00	0.00E+00	-1.07E-03
	NHWD	kg	2.84E-01	2.46E-02	0	9.34E-04	6.96E-03	5.00E-03	1.01E-01	-3.36E-02
	RWD	kg	2.39E-05	2.57E-07	0	5.48E-06	7.28E-08	0.00E+00	0.00E+00	-3.98E-06

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9.0 E-03 = 9.0*10⁻³ = 0.009"

End of life - Output flow										
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
	CRU	kg	0.00E+00	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	MFR	kg	6.08E-06	0.00E+00	0	0.00E+00	0.00E+00	8.96E-01	0.00E+00	0.00E+00
	MER	kg	1.99E-07	0.00E+00	0	0.00E+00	0.00E+00	5.00E-03	0.00E+00	0.00E+00
	EEE	MJ	1.21E-06	0.00E+00	0	0.00E+00	0.00E+00	4.95E-06	0.00E+00	0.00E+00
	EET	MJ	1.83E-05	0.00E+00	0	0.00E+00	0.00E+00	7.49E-05	0.00E+00	0.00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9.0 E-03 = 9.0*10⁻³ = 0.009"

Biogenic Carbon Content		
Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0.00E+00
Biogenic carbon content in accompanying packaging	kg C	9.10E-03

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Source	Amount	Unit
Electricity, China (kWh)	ecoinvent 3.6	1102.91	g CO ₂ -eq/kWh

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

Not relevant

Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products									
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWPIOBC	kg CO ₂ -eq	8.79E-01	5.70E-02	0	5.73E-02	1.62E-02	1.11E-02	8.40E-04	-1.49E-01

GWPIOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21

Graafland and Iversen, (2022) EPD generator for NPCR 013 Part B for Steel and Aluminum, Background information for EPD generator application and LCA data, LCA.no report number: 08.22

NPCR Part A: Construction products and services. Ver. 2.0. April 2021, EPD-Norge.

NPCR 013 Part B for Steel and Aluminium Construction Products , Ver. 4.0, 06.10.2021, EPD Norway.

 Powered by EPD-Norway	Program operator and publisher EPD-Global Postboks 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-global.com
 Let's connect	Owner of the declaration: Pretec Norge AS Kampenesmosen 3, 1739 Borgenhaugen, Norway	Phone: (+47) 69 10 24 60 e-mail: post@pretec.no web: www.pretec.no
	Author of the Life Cycle Assessment LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	Developer of EPD generator LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	ECO Platform ECO Portal	web: www.eco-platform.org web: ECO Portal