Skjøtehylse til Glassfiberstag stag stål ubehandlet

Skjøtehylse til GFRP ankerstag. Leveres i stålmaterialet 20Cr4 med ubehandlet overflate.

Lagerprogram:
Skjøtehylse GFRP R20x120 Ø30 stål UB
Skjøtehylse GFRP R25x150 Ø35 stål UB

Teknisk informasjon:
Høyregjenget etter ISO 10208 / ISO 1720 (R-gjenge). Hylse er samtestet med stag og skjøtehylsens kapasitet overstiger Pretec sine GFRP stag i samme dimensjon, ved strekk definerer styrken av glassfiberstagets gjenge kapasiteten.

Dimensjon	Utvendig mål Ø (mm)	Total Lengde (mm)	Innskruings lengde (mm)	Vekt kg /stk	Min. bruddstyrke gjenge (kN)
R20x120	30	120	55	0,35	80
R25x150	35	150	70	0,76	180

Tilbehør
Glassfiberstag Ø20
Glassfiberstag Ø25

Coupler for Glassfiber anchor Steel Plain

Coupler for GFRP anchor. Delivered with steel material 20Cr4 with plain surface.

Stock programme:
Coupler GFRP R20x120 Ø30 steel Plain
Coupler GFRP R25x150 Ø35 steel Plain

Technical information:
Right hand threaded acc. ISO 10208 / ISO 1720 (R-thread). Tensile strength of coupler exceeds nominal tensile strength of Glassfiber anchor in corresponding dimension. The sleeve, when jointly tested with the rod, has a capacity exceeding that of Pretec's GFRP rods of the same dimension, with the tensile strength determined by the threaded capacity of the fiberglass rod.

Dimension	Outer dia. Ø (mm)	Length (mm)	Thread engagement (mm)	Weight kg /pcs	Min. tensile strength thread (kN)
R20x120	30	120	55	0,35	80
R25x150	35	150	70	0,76	180

Accessories
Glassfiber anchor Ø20
Glassfiber anchor Ø25